

## Key Specifications/Special Features:

- Features:
  - ALI solution (M3328F)
  - Compatible with DVB-S/MPEG-2
  - High-quality pictures
  - Power off memory
  - Adjustable RF modulator
  - Separate tuner V76A
  - Software can be upgraded
  - Box-to-Box upgrading supported
  - Data port: DB9F/DB9M
  - Highly reliable switch power
  - Store 1000 programs (Max)
  - Multiple languages
- Specification:
  - Tuner:
    - Input frequency range: 950 - 2,150MHz
    - Input level: -79 - -11dBm
    - Input connector: 75ΩF type female
    - IF band width: 27 - 36MHz
    - LNB power: 13/18V
    - LNB tone switch control: 22KHz tone/ DiSEqC 1.0/1.2
  - Demodulator:
    - Decode format: MPEG-2
    - Symbol rate: 2-45Mbps
    - Wave format: QPSK(scpc, mcpc)
    - Bit rate: ≤15Mbps
  - Video:
    - Output format: I NTSC/PAL-B/ G/I/D/K
    - Video output level: 1V±(20mV)p-p
    - Resolution: 720 x 576
    - PAL: 720 x 480 at NTSC
    - Aspect rate: 4:3
    - Output connector: RCAx6/S-port x1/RFx1
    - Output type: CVBS/Y-C
  - Audio:
    - Frequency response: 20Hz to 20KHz Hi-Fi
    - Output type: monophonic/stereo
    - Sampling rate: 32/44.1/48KHz