

Key Specifications/Special Features:

- Features:
 - ALI solution (M3328F)
 - Compatible with DVB-S/MPEG-2
 - High-quality pictures
 - Power off memory
 - Adjustable RF modulator
 - Separate tuner V76A
 - Software can be upgraded
 - Box-to-Box upgrading supported
 - Data port: DB9F/DB9M
 - Highly reliable switch power
 - Store 1000 programs (Max)
 - Multiple languages
- Specification:
 - Tuner:
 - Input frequency range: 950 - 2,150MHz
 - Input level: -79 - -11dBm
 - Input connector: 75ΩF type female
 - IF band width: 27 - 36MHz
 - LNB power: 13/18V
 - LNB tone switch control: 22KHz tone/ DiSEqC 1.0/1.2
 - Demodulator:
 - Decode format: MPEG-2
 - Symbol rate: 2-45Mbps
 - Wave format: QPSK(scpc, mcpc)
 - Bit rate: ≤15Mbps
 - Video:
 - Output format: I NTSC/PAL-B/ G/I/D/K
 - Video output level: 1V±(20mV)p-p
 - Resolution: 720 x 576
 - PAL: 720 x 480 at NTSC
 - Aspect rate: 4:3
 - Output connector: RCAx6/S-port x1/RFx1
 - Output type: CVBS/Y-C
 - Audio:
 - Frequency response: 20Hz to 20KHz Hi-Fi
 - Output type: monophonic/stereo
 - Sampling rate: 32/44.1/48KHz