



WAE-302 AUDIO AUTOMATIC CONTROL EQUALIZER

FEATURES

- Variance of Input Level: $\pm 18\text{dB}$; Tolerance of Output level: $\pm 0.5\text{dB}$
- Output Level: 0~2 Vp-p (1Vp-p Preset in Factory), 1 KHz
- Automatic Audio Equalization without Tuning
- Gain Compressor from Peak to 0dB/0V; 8 Seconds
- Audio Connection Possibility: 6 Stereo Channels or 12 Mono Channels
- Professional Calibration Signal: 1 KHz

FRONT PANEL

AGC Indicator	Yes
CAL Indicator	Yes
Input Indicator	Yes
AGC Select Switch	Yes
CAL Select Switch	Yes
Output Level Adjustable	Yes

REAR PANEL

Mode	Dual Mono or Stereo
------	---------------------

POWER

Input Power	110V AC/60Hz or 175~230V AC/50Hz
-------------	-------------------------------------

GENERAL

Dimension	19"(L) \times 9-3/4"(W) \times 1-3/4"(H)
Weight	8 Lbs
Packing	5 Sets/Carton/16Kgs/3.12 cuft

SPECIFICATIONS

INPUT SECTION

CMRR	40dB (Min.)
Input Impedance	100K Ω Unbalance





OUTPUT SECTION

Output Impedance	600 Ω Unbalance
Output Level, Peak	10dB, Adjustable on Front Panel

OVERALL PERFORMANCE

Distortion	0.25% Max.
S/N Ratio	80dB
Frequency Response	50Hz~20KHz, $\pm 0.5\text{dB}$

FRONT PANEL OPERATION

- ① ALC ON  : Control the Output Level as Preset
- ALC OFF  : Release the Output Level Control
- ② CAL ON  : With 1 KHz Output
- CAL OFF  : Without 1 KHz Output
- ③ Output Level Adjustable: Adjust Output Level